



POWER &amp; DATA DISTRIBUTION / DATA DISTRIBUTION

# MD94DDU DATA DISTRIBUTION UNIT

SKU: MNE-0069

## FEATURES

- **Designed for NMEA Data Distribution**
- **2x NMEA 0183 Inputs**
- **9x NMEA 0183 Outputs**
- **Inputs mappable to Outputs**
- **Outputs provide Power and Remote Dimmer Connections**
- **Single / Dual 24 V dc Supply (Main and Backup)**
- **Rugged Marinised Aluminium Enclosure**
- **MD94DDU+ includes 10 extra pass-through terminals for user options**

## OVERVIEW

The MD94DDU is a NMEA 0183 Data Distribution Unit able to take two independent NMEA 0183 inputs and transmit a buffered NMEA 0183 output to up to nine devices.

The MD94DDU can be daisy chained with another MD94DDU to increase the number of available outputs if required. In this way, digital heading data (ship's heading) or any other NMEA 0183 data may be conveniently relayed to any location on a vessel.

The MD94DDU offers a NMEA 0183 Distribution solution for most locations. Finished in Jet Black (RAL9005) Fine-texture Powder Coat to complement other bridge marine navigation equipment.

The MD94DDU+ also includes 10 extra pass-through terminals for user defined wiring options.

The MD94DDU NMEA Data Distribution Unit from Marine Data: flexible in application, easy to install and simple to maintain.

## APPLICATIONS

- Allows the Distribution of individually buffered NMEA 0183 signals to multiple devices
- Allows Common Dimming of all connected instruments

## ACCESSORIES

- [MD01/PMD](#) - Rotary Remote Dimming Control

## RELATED PRODUCTS

- Any NMEA 0183 (IEC61162-1) compliant device
- Transmitting Heading Device (THD) Systems ([TMC](#) and [EMC](#))



## PHYSICAL

<b>Weight:</b>	1.5 kg
<b>Dimensions:</b>	H 254 mm; W 254 mm; D 70 mm
<b>Mounting:</b>	M6 Fixings on 220 mm sq' centres
<b>Connections:</b>	Multicore cable through M20 watertight gland to internal screw terminals
<b>Construction:</b>	Aluminium alloy enclosure
<b>Finish:</b>	Jet Black (RAL9005) Fine-texture Powder Coat

## ELECTRICAL

<b>Power Supply:</b>	Single / Dual (Main / Backup) Supplies 24 V dc, 2.5 W nominal (21-31 V dc)
<b>Data Inputs:</b>	2x NMEA 0183 (IEC 61162-1)
<b>Data Outputs:</b>	9x NMEA 0183 (IEC 61162-1; IEC 61162-2)
<b>Power Outputs:</b>	24 V dc; 500 mA (max)
<b>Data Sentences:</b>	Re-transmitted as received (Buffered)

## OPERATIONAL


<b>Performance:</b>	NMEA 0183 Distribution with Buffer Function 4800 - 38400 Baud
<b>MTBF:</b>	>30,000 hours

## ENVIRONMENTAL

<b>IEC 60945 Equipment Category:</b>	Protected Area
<b>Operating temp:</b>	-15°C to +55°C
<b>Storage Temp:</b>	-25°C to +70°C
<b>Compass Safe Distance:</b>	Standard: 20cm Steering: 20cm
<b>RoHS:</b>	Compliant

## APPROVALS

<b>Complies with:</b>	IEC 60945; IEC 61162-1
<b>Type Approval:</b>	DNV



Copyright © 2022 Marine Data Systems Ltd. - MD94DDU Datasheet v06r04

Vittlefields Technology Centre, Forest Road, Newport, Isle of Wight, United Kingdom. PO304LY  
 Marine Data Systems Ltd. reserves the right to make changes to its products and specifications without prior notice.